

HNL STEP LIGHT SERIES

HNLHH/HNLHL/HNLOF/HNLVH

FEATURES:

- Intended for Healthcare Settings, Patient Rooms, Surgical Suites, Commercial Settings, Lobbies, Schools, and more
- Four faceplate options: horizontal or vertical hood, louver, and open frame
- Manufactured in durable die cast aluminum
- Available in white or amber color temperatures
- Optional photocell or occupancy sensor with select faceplates



HNLHH

RELATED PRODUCTS:

- [HNL Step Light Quick Ship Ordering Options](#)
- [StarStep SNL3](#)



SPECIFICATIONS

CONSTRUCTION: Durable die cast aluminum material. Available with four different faceplates: Horizontal Hood, Horizontal Louver, Open Frame (can be installed vertically or horizontally), and Vertical Hood.

LED: Available in three white color temperatures 3000°K, 4000°K and 5000°K. Amber LED's available. Consult factory for additional LED colors.

ELECTRICAL: Integrated embedded driver (3W). Optional dimming.

FINISH: White antimicrobial finish (standard). Custom color available, must specify RAL number and if antimicrobial finish is needed (set-up fees may apply).

INSTALLATION: Recessed installation. JBox and hardware by others.

WARRANTY: Limited five (5) year warranty.

LABEL: Fixture is certified to UL standards for Wet Location rating (under covered ceiling).

HNL STEP LIGHT SERIES

HNLHH/HNLHL/HNLOF/HNLVH

ORDERING INFORMATION

EXAMPLE: HNL-HH-30-UN-NF-ND-AM

SERIES	FACEPLATE	COLOR TEMP.	VOLTAGE	OPTIONS
HNL			UN	

HH = Horizontal Hood*	30 = 3000°K	UN = Universal (120V-277V)	NF = None
HL = Horizontal Louver	40 = 4000°K		PC = Photocell*
OF = Open Frame**	50 = 5000°K		OC = Occupancy Sensor**
VH = Vertical Hood	LA = Amber LED*		

* Only faceplate that can be used with Occ Sensor/ Photocell. *Not available with OC.
 **Can be installed horizontally or vertically.

*Can only be used with HH Faceplate. PC & OC cannot be used together.
 ** OC N/A with Amber. Can only be used with HH Faceplate. PC & OC cannot be used together.

DIMMING	FINISH

ND = None AM = Antimicrobial White
 DM = 0-10V dimming with 10-100% range CC = Custom Color*

*Must specify RAL number at time of order and if antimicrobial finish is needed. Subject to set-up fees.

HNL STEP LIGHT SERIES

HNLHH/HNLHL/HNLOF/HNLVH



PERFORMANCE DATA*

*Data is with 80 CRI chip. LEDs are frequently updated therefore values may change without notice.

MODEL	COLOR TEMP.	LUMENS DELIVERED	EFFICACY (lm/W)	INPUT POWER (W)
HNL-OF	3000°K	250	66	3.8
	4000°K	240	63	3.8
	5000°K	253	67	3.8
	Amber LED	170	45	3.8
HNL-VH	3000°K	92	24	3.8
	4000°K	82	22	3.8
	5000°K	95	25	3.8
	Amber LED	61	16	3.8
HNL-HH	3000°K	130	34	3.8
	4000°K	120	32	3.8
	5000°K	133	35	3.8
	Amber LED	88	23	3.8
HNL-HL	3000°K	124	33	3.8
	4000°K	114	30	3.8
	5000°K	127	33	3.8
	Amber LED	85	22	3.8

DIMENSIONAL DATA

