TRUSTED, TOUCHLESS HAND DRYING SOLUTIONS

XLERATOReco®
High Speed. No Heat. 500 Watts.

XLERATOR®
Original. Patented. Still The Best.

ThinAir®
Surface Mounted. Slimmer Profile.

CUSTOM COVERS

ENHANCED FEATURES

- Available with Electrostatic HEPA (eHEPA®) Filtration System
- Adjustable Speed and Sound Control
- Multi-Voltage Options: 110-120V Or 208-277V
- Adjustable Heat Settings - High, Medium, Low & Off
- Externally Visible Service LED

BENEFITS OF EXCEL'S HIGH-SPEED, ENERGY-EFFICIENT HAND DRYERS

- Touchless, Hygienic Hand Drying Solution
- 95% Cost Savings Vs. Paper Towels
- Made In USA® Certified
- Reduces Restroom Maintenance, Freeing Up Maintenance Staff
- Reduces Carbon Footprint of Hand Drying up to 94%
- 80% Less Energy Than Conventional Hand Dryers

XLERATOR

ORIGINAL. PATENTED. STILL THE BEST.

- Reliable, A Workhorse!
- 7-Year Limited Warranty
- Wattage: 1490W (Heat On) - 425W (Heat Off)

XLERATORECO

HIGH SPEED. NO HEAT. 500 WATTS.

- Innovative No Heat Technology
- 7-Year Limited Warranty
- Wattage: 425W-530W - Install Multiple Units On One Circuit

THINAIR

SURFACE MOUNTED. SLIMMER PROFILE.

- Meets Accessibility Standards
- 5-Year Limited Warranty
- Wattage: 950 Watts (Heat On) - 300 Watts (Heat Off)

FEATURES	XLERATOR	XLERATOReco	ThinAir
DRY TIME	8 Seconds	10 Seconds	14 Seconds
ENERGY USE	3.7 Wh[1]	1.7 Wh[1]	3.7 Wh[1]
ADJUSTABLE SOUND	65 - 75 dB	65 - 75 dB	69 - 73 dB
WATTS	1490W (Heat On), 425W (Heat Off)	425W-530W	950W (Heat On), 300W (Heat Off)
VOLTS / AMPS	110-120V 11.3-12.2A 60Hz 208-277V 5.6-6.2A 60Hz 230V 6.1A 50Hz	110-120V 4.3-4.5A 60Hz 208-277V 2-2.2A 60Hz 230V 2.2A 50Hz	110-120V 7.2-7.8A 60Hz 208-277V 3.6-4A 60Hz 230V 3.9A 50Hz
CUSTOM COVERS	✓	✓	✓
ELECTROSTATIC HEPA (eHEPA®) FILTRATION	Washable Pre-Filter Optional Electrostatic HEPA (eHEPA®) Filtration System	Washable Pre-Filter Optional Electrostatic HEPA (eHEPA®) Filtration System	Washable Pre-Filter Optional Electrostatic HEPA (eHEPA®) Filtration System
MADE IN USA	✓	✓	✓

SMART EPD CERTIFIED
ENVIRONMENTAL PRODUCT DECLARATION

Smart EPD® verifies Environmental Product Declarations (EPDs) for consistency with the LCA and conformance with global Product Category Rules (PCR) for hand dryers. UL Environment published the first global PCR for hand dryers. Third-party testing to these guidelines documents a product's environmental impact over its lifecycle. This impact is detailed in Environmental Product Declarations, enabling specifiers and buyers to make true apples-to-apples comparisons and more informed product selections. Excel Dryer received the industry's first certified EPDs.

TESTED TO PCR GUIDELINES



ACCESSORIES & OPTIONS

- 1.1" Noise Reduction Nozzle
- Electrostatic HEPA (eHEPA®) Filtration System
- Recess Kit
- Antimicrobial Wall Guards
- Custom Covers
- XChanger® Paper Towel Dispenser Retrofit Kit

[1]Dry time and energy use testing performed by SGS International on standard XLERATOR/XLERATOReco Hand Dryers with 0.8" nozzle/standard ThinAir Hand Dryers to 0.25g or less of residual moisture, pursuant to the UL Environment Global Product Category Rules (PCR) for Hand Dryers.