

Disposable Cubicle Curtain

Suggested Specification



- Made from low cost fabrics
- Can be disposed of after use
- NFPA 701 Compliant
- Antibacterial (mesh curtains only)
- Self Auditing Label
- Individually Packaged
- 12 curtains per case

Disposable Cubicle Curtain

Suggested Specification

PART 1 - GENERAL

1.01 SUMMARY

A. Privacy Curtain

1.02 SECTION INCLUDES

A. Disposable Cubicle Curtains

1.03 REFERENCES

A. National Fire Protection Association (NFPA)

1.04 SYSTEM DESCRIPTION

A. Performance Requirements: Provide disposable privacy curtains that conform to the following requirements of regulatory agencies and the quality control of Clickeze, Inpro Corporation.

1. Fire Performance Characteristics: Provide curtains that conform with NFPA 701, Fire Tests for Flame and Resistant Textiles and Films.

1.05 SUBMITTALS

A. Product Data: Manufacturer's printed product data for each type of disposable privacy curtain specified.

B. Fabric Samples: Swatch cards of fabric samples illustrating fabric color and weave.

1.06 DELIVERY, STORAGE AND HANDLING

A. Deliver materials in unopened factory packaging to the jobsite.

B. Inspect materials at delivery to assure that specified products have been received.

C. Store in original packaging in a climate controlled location away from direct sunlight.

1.07 PROJECT CONDITIONS

A. Environmental Requirements: Products must be installed in an interior climate controlled environment.

1.08 WARRANTY

A. Standard Clickeze Limited Warranty against material and manufacturing defects.

PART 2 - PRODUCTS

2.01 MANUFACTURER

A. Acceptable Manufacturer Clickeze, Inpro Corporation,

PO Box 406 Muskego, WI 53150 USA;
Telephone: 800-222-5556, Fax: 888-715-8407,
Internet address: <http://www.inprocorp.com>

B. Substitutions: Not permitted

C. Provide all privacy curtains from a single source.

2.02 MATERIALS

A. Disposable Privacy Curtain

1. Fabric: Provide 100% non-woven polypropylene with a thickness of 120 GSM.

2. Open Mesh Cloth: Provide curtain heading of open weave polyester mesh material with 1/2" (12.7mm) holes to permit air and steam circulation. Mesh is to be flame retardant.

3. Snap Panel: Panels shall be 66" x 66" - no mesh - 120 GSM.

2.03 FINISH AND COLOR

A. Disposable Cubicle Privacy Fabric: Select material color from manufacturer's standard disposable material selection.

B. Open Mesh Cloth: Provide curtain mesh material in white.

2.04 FABRICATION

A. Disposable Privacy Curtain

1. Standard sizes and case quantity

a. 94" (2.39m) w x 93" (2.36m) h, 12 curtains per case.

b. 94" (2.39m) w x 81" (2.06m) h, 12 curtains per case

Each curtain includes a Velcro tie back.

Curtains are individually wrapped in plastics sleeves.

2. Curtain Heading: Heading shall have open mesh cloth, to the same width as the curtain fabric. Heading shall include 3/4" (19mm) white plastic grommets, 5.9" (149.9mm) on center for carriers. Mesh shall be sewn with fabric on sides of mesh and top of mesh banding (where grommets are placed). Mesh is "framed".

B. Disposable Snap Panels

1. Curtain Snaps:

a. Bottom Mesh Footer: Provide rustproof, nickel-plated brass snaps with off-white plastic cover spaced 4.6" (117mm) on center and machined into bottom mesh footer.

b. Top Curtain Header: Provide rustproof, nickel-plated brass, double-sided snaps spaced 4.6" (117mm) on center and machined into top curtain header.

C. Snap Panel Privacy Curtain

1. Standard sizes and case quantity

a. 66" (1.68m) w x 66" (1.68m) h, 12 curtains per case.

b. Disposable Fabric shall be 100% Polypropylene.

Thickness - 100 GSM.

PART 3 - EXECUTION

3.01 EXAMINATION

A. Examine areas and conditions in which the cubicle tracking systems will be installed.

1. Complete all finishing operations, including painting, before beginning installation of cubicle tracking system materials.

2. Verify that surfaces and above ceiling supports are ready to receive work.

3.02 PREPARATION

A. General: Prior to installation, clean substrate to remove dust, debris and loose particles.

3.03 INSTALLATION

A. General: Locate the cubicle track as indicated on the approved detail drawing for the appropriate substrate and in compliance with the Clickeze installation instructions.

B. Installation of Cubicle Tracking Systems:

1. Install cubicle track, secure, rigid, and true to ceiling line.

2. Slide carriers onto the track.

3. Install end cap or stop device.

4. Secure or suspend track to ceiling system. Install with mechanical fasteners or Gridclips.

5. Install curtains on carriers ensuring smooth operation.

6. Remove plastic sleeve from curtain.

C. Snap Panel Curtain Option:

1. Attach mesh to cubicle track carriers.

2. Snap curtain panels onto mesh from each end.

3. Overlap curtain panels at desired width for complete privacy then snap to the end of panel

4. Place adhesive velcro disc at bottom of panel overlap for added privacy when using disposable snap panels.

3.04 CLEANING

A. At completion of the installation, remove any debris and clean surfaces in accordance with the Clickeze clean-up and maintenance instructions.